

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 791 762 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
27.08.1997 Bulletin 1997/35

(51) Int. Cl.⁶: F16C 33/66, F16C 17/26

(21) Application number: 96306082.7

(22) Date of filing: 20.08.1996

(84) Designated Contracting States:
DE FR GB IT NL

(30) Priority: 07.09.1995 US 525298

(71) Applicant: QUANTUM CORPORATION
Milpitas California 95035 (US)

(72) Inventors:
• Polch, Ewaryst Z.
Monument, Colorado 80132 (US)

• Williams, Carl D.
Colorado Springs, Colorado 80907 (US)

(74) Representative: Goodman, Christopher et al
Eric Potter & Clarkson
St. Mary's Court
St. Mary's Gate
Nottingham NG1 1LE (GB)

(54) Bearing with particle trap

(57) A hydrodynamic bearing (10) journaling a shaft (12) includes a rotatable bushing (16) journaling the shaft (12) and thrust plates (13) on the shaft (12) at opposite ends of the bushing (16). The bushing (16) is encased in a cylindrical sleeve (15). Lubricant containing clearance spaces (26,32) are formed between the shaft (12), bushing (16), sleeve (15), and thrust plates (13). An internal radial chamber (26) in the sleeve (15) between the bushing (16) and sleeve (15) stores lubricant and collects foreign particles (29). Radial ports (28) through the bushing (16) provide for flow of lubricant between the journal bearing (14) and the shaft (12) and thrust plates (13).




Fig. 3

EP 0 791 762 A2

Description

BACKGROUND OF THE INVENTION

Field of the Invention.

The present invention relates to precision journal bearings for high speed precision drive shafts. More particularly, the present invention relates to high speed, internally lubricated, hydrodynamic journal or spindle bearings finding particular but not necessarily exclusive utility for magnetic media drive mechanisms.

Description of the Prior Art.

Bearings of the character embodying the present invention are disclosed in U.S. Pat. 4,795,275, issued January 3, 1989, to F. Titcomb and J. Cordova, for "Hydrodynamic Bearing." Such bearings are also disclosed in U.S. Pat. 4,596,474, issued June 24, 1986, to F. Van Roemburg; U.S. Pat. 4,726,693, issued February 23, 1988, to J. Anderson and R. Slegler; U.S. Pat. 5,067,528, issued November 26, 1991, to F. Titcomb and J. Cordova; and U.S. Pat. 5,112,142, issued May 12, 1992, to F. Titcomb and J. Cordova. Such hydrodynamic bearings include a bearing sleeve with an internal journal bushing press fitted therein and in which is journaled a precision shaft, with provision between the shaft and bushing for incorporating lubricants. Thrust bearings are mounted on the shaft on opposite sides of the bushing. Flats are conventionally machined on the exterior surface of the bushing before press or shrink fit assembly into the sleeve to provide axially extending pressure equalizing lubricant passages in the bearing, with ports or passages through the bushing for conducting lubricant to the shaft journaled in the bushing and to the thrust bearings.

OBJECTS OF THE INVENTION

It is the principal object of the present invention to provide an improved hydrodynamic bearing.

More specifically, it is an object of the present invention to provide an improved hydrodynamic bearing having a trap for collecting foreign particles from the lubricant.

It is another object of the present invention to provide an improved hydrodynamic, internally lubricated shaft and journal sleeve bearing structure having enhanced particle removal characteristics, which is readily constructed and assembled, rugged in use, and suitable for high speed equipment such as magnetic media disk drives.

DESCRIPTION OF THE DRAWINGS

Fig. 1 is an elevation view of a hydrodynamic bearing embodying the present invention.

Fig. 2 is a vertical section view taken substantially

in the plane of line 2-2 on Fig. 1.

Fig. 3 is a horizontal section view taken substantially in the plane of line 3-3 on Fig. 1.

Fig. 4 is a perspective view of a journal bearing embodying the present invention, with parts cut away for clarity.

Fig. 5 is a perspective view of a sleeve portion of the bearing shown in Fig. 4 with, parts cut away for clarity.

Fig. 6 is a perspective view of a bushing portion of the bearing shown in Fig. 4 with, parts cut away for clarity.

SUMMARY OF THE INVENTION

In accordance with the foregoing objects, the present invention is embodied in a hydrodynamic bearing comprising an outer cylindrical sleeve having a bushing, with a smaller inside diameter, press or shrink fitted therein, and shaft journals rotatably journaled in the bushing. A pair of thrust plates are mounted on the shaft and rotatably and sealingly coact with radially extending faces on the smaller diameter portion of the bushing. The clearance spaces between the bushing, shaft journals and thrust plates, and the axial passages between the bushing and sleeve are filled with a lubricant. The external faces of the thrust plates are exposed to the air. The inner diameter portion of the sleeve includes a circumferential channel which, with radial ports through the bushing, defines a lubricant chamber which contains lubricant and which collects and retains foreign particles from the lubricant and bearing.

DESCRIPTION OF THE PREFERRED EMBODIMENT

The present invention is embodied in an internally lubricated journal bearing 10 incorporating a sleeve and bushing assembly 11 rotatably journaling a shaft 12, with thrust plates 13 supported on opposite ends of the shaft in operative coaction with the sleeve and bushing assembly 11. The shaft 12 defines spaced spools or journals 14. The thrust plates 13 are mounted on the shaft 12 adjacent to each shaft spool journal 14. The thrust plates 13 may be press fit onto the shaft 12 to provide a lubricant tight seal therebetween.

The journal bearing sleeve and bushing assembly 11 is formed by an external sleeve 15 having an internal bushing 16 press or shrink fit mounted therein. The internal bushing 16 defines an inner, axially extending journal bearing surface 18 within which the shaft journals 14 are rotatably supported or journaled. At its opposite ends, the internal bushing 16 defines radially extending thrust surfaces 19 in opposing relationship with internal radial surfaces 20 on the thrust plates 12. Axially extending flats 21 machined or formed on the external surface 22 of the bushing 16 define, with the inner surface 24 of the sleeve 15, axially extending, lubricant containing, pressure equalization passages 25.

For collecting foreign particles 29 in the lubricant, such as tiny metal particles, an internal lubricant reservoir in the form of an internal circumferential channel 26 is defined in the inner surface 24 of the sleeve 15. A plurality of radial ports 28 extend from the inner surface 18 of the bushing 16 to the outer surface 22 thereof, and open into the lubricant reservoir channel 26 defined in the sleeve 15, thereby providing a lubricant passage from the reservoir channel 26 to the shaft journals 14 and inner bushing surface 18. Because of centrifugal forces on the bearing and lubricant, foreign particles 29 tend to collect and are retained in the internal lubricant reservoir channel 26. The surface of the channel 26 may be rough cut to assist in particle retention.

Lubricant is also contained in a circumferential shaft recess or channel 30 which extends axially between the shaft journals 14. The shaft journals 14 define axially extending circumferential bearing surfaces 31 which operatively coact with the internal surface 18 of the bushing 16 and the lubricant to journal the shaft 11 in the journal bearing bushing 10. Lubricant is contained in the journal bearing structure in a clearance chamber 32 generally formed and defined between the internal surface 18 of the bushing 16 and the external surface 31 of each shaft journal 14, which chamber 32 includes the shaft recess channel 30 and the clearance spaces defined between the facing thrust surfaces 19 and 20 of the bushing 16 and the thrust plates 12, respectively. Lubricant is supplied to the internal chamber 32 thus defined from the reservoir channel 26 defined in the sleeve 15, through the radial ports 28 or in the bushing 16, free of harmful particles 29.

While a certain illustrative embodiment of the present invention has been shown in the drawings and described above in considerable detail, it should be understood that there is no intention to limit the invention to the specific modification or embodiment disclosed. On the contrary, the intention is to cover all modifications, alternative constructions, equivalents and uses falling within the spirit and scope of the invention as expressed in the appended claims.

Claims

1. A hydrodynamic bearing for journaling a shaft, comprising a bushing supported in a sleeve and journaling said shaft, thrust plates on said shaft at opposite ends of said bushing, said bushing, shaft and thrust plates defining a clearance space therebetween for retaining a lubricant, said sleeve and bushing defining a particle collecting lubricant reservoir channel therebetween, and said bushing defining a port between said channel and said clearance space for supplying lubricant free of particles to said clearance space.
2. A bearing as defined in claim 1 further comprising axially extending pressure equalization passages between said sleeve and said bushing.

3. A hydrodynamic bearing and shaft assembly comprising a cylindrical bushing encased in a cylindrical sleeve, a shaft journaled in said bushing and including a journal having an outer surface forming a clearance space with respect to the smaller inner surface of said bushing, said clearance space being filled with a lubricant, characterized in that said sleeve defines an inner circumferential channel between said sleeve and said bushing, and said bushing defines radial ports therethrough in communication with said channel and said shaft.
4. A bearing as defined in claim 2 wherein the surface of said channel is rough to retain foreign particles.
5. A bearing as defined in claim 3 wherein said bearing further comprises pressure equalization passages between said sleeve and said bushing.




Fig. 1




Fig. 2




Fig. 4




Fig. 5





Fig. 6



(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 791 762 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
09.12.1998 Bulletin 1998/50

(51) Int. Cl.⁶: **F16C 33/66, F16C 17/26**

(43) Date of publication A2:
27.08.1997 Bulletin 1997/35

(21) Application number: **96306082.7**

(22) Date of filing: **20.08.1996**

(84) Designated Contracting States:
DE FR GB IT NL

(30) Priority: **07.09.1995 US 525298**

(71) Applicant: **QUANTUM CORPORATION**
Milpitas California 95035 (US)

(72) Inventors:
• **Polch, Ewaryst Z.**
Monument, Colorado 80132 (US)

• **Williams, Carl D.**
Colorado Springs, Colorado 80907 (US)

(74) Representative:
Goodman, Christopher et al
Eric Potter Clarkson,
Park View House,
58 The Ropewalk
Nottingham NG1 5DD (GB)

(54) Bearing with particle trap

(57) A hydrodynamic bearing (10) journaling a shaft (12) includes a rotatable bushing (16) journaling the shaft (12) and thrust plates (13) on the shaft (12) at opposite ends of the bushing (16). The bushing (16) is encased in a cylindrical sleeve (15). Lubricant containing clearance spaces (26,32) are formed between the shaft (12), bushing (16), sleeve (15), and thrust plates (13). An internal radial chamber (26) in the sleeve (15) stores lubricant and collects foreign particles (29). Radial ports (28) through the bushing (16) provide for flow of lubricant between the journal bearing (14) and the shaft (12) and thrust plates (13).




Fig. 3

EP 0 791 762 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 96 30 6082

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
Y,D	US 4 795 275 A (FITCOMB FORREST ET AL) 3 January 1989 * column 3, line 23 - column 4, line 63; figures 1-5 *	1-3,5	F16C17/26 F16C33/10
Y	PATENT ABSTRACTS OF JAPAN vol. 009, no. 256 (M-421), 15 October 1985 & JP 60 104814 A (NDC KK), 10 June 1985 * abstract *	1,2	
A	---	4	
Y	US 3 917 362 A (STEDMAN ROBERT N) 4 November 1975	3,5	
A	* column 2, line 34 - column 3, line 4; figure 1 *	1,2,4	
A	GB 268 034 A (FREDERICK LEONARD BALL, FRANK MOULTON, L. W. TOOLS COMPANY LIMITED) 24 March 1927 * page 3, line 37 - line 103; figure 1 *	1,3	
A	US 3 343 893 A (HARRY HALL) 26 September 1967 * the whole document *	1,3	TECHNICAL FIELDS SEARCHED (Int.Cl.6) F16C
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 22 October 1998	Examiner Fischbach, G
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03/82 (P04C01)